
ALSH-2DX THRU 8 UV STERILIZERS



*REPLACE UV LAMP EVERY 11 MONTHS REPLACEMENT UV LAMP PART#: UV-BULB-095W-2

ALSH UV STERILIZER SPECIFICATIONS														
·	NO. OF LAMP /WATTS	VOLTS	AMPS / WATTS	W	W2	W3	W4	*H	*S TANDARD WATER IN / OUT WATER CONNECTIONS	MAXIMUM WATER FLOW RATE (GPM) AT UV INTENSITY µWsec/cm2 @ 90% TRANSMISSIBLITY 85% AT END OF LAMP LIFE				
MODEL NO.														
										30K	45K	60K	90K	120K
ALSH-2DX	2 / 190	115	1.8 / 207	30 1/2"	6 1/4"	23 1/4"	13"	17"	2" UNION	80	53	40	27	20
ALSH-3DX	3 / 285	115	2.5 / 287	30 1/2"	4 3/4"	20 3/4"	15"	23 1/4"	3"UNION	151	101	76	50	38
ALSH-4DX	4/380	115	3 / 345	30 1/2"	4 3/4"	20 3/4"	15"	23 1/4"	3" UNION	213	142	106	71	53
ALSH-5DX	5 / 475	115	4.5 / 517	30 1/2"	5 1/2"	21 5/8"	15"	20 5/8"	4" FLANGE	282	188	141	94	70
ALSH-6DX	6 / 570	115	5.4 / 621	35 7/8"	7 1/2"	21"	22"	27 3/4"	6" FLANGE	372	248	186	124	93
ALSH-8DX	8 / 760	115	7.2 / 828	35 7/8"	7 1/2"	21"	22"	27 3/4"	6"FLANGE	533	355	266	177	133

· SHADED AREAS HAVE WATER VELOCITIES GREATER THAN 5 FT / SEC.

· CONTACT AQUA LOGIC FOR LARGER CONNECTION SIZES.

DX MODEL INCLUDES:

· POWER ON / OFF SWITCH.

· POWER AND OVER TEMPERATURE LED INDICATORS LIGHTS.

· LCD HOUR METER.

· OVER TEMPERATURE AIR AND WATER CUTOUTS.

· NEMA 4X RATED CONTROL BOX.

· INDIVIDUAL LAMP INDICATOR LIGHTS.

· UL-508A RATED CONTROL BOX. (OPTIONAL)

*NOTES:

· FLOW RATES BASED ON "END OF LIFE", LAMP OUTPUT OF 85% AT 9000 HOURS.

· ALL DIMENSIONS ARE APPROXIMATE AND SUBJECT TO CHANGE

WITHOUT NOTICE.

· ALL UNITS 50 PSIG MAXIMUM OPERATING PRESSURE. OTHER WATER CONNECTIONS SIZES ARE AVAILABLE.

> DESCRIPTION * COPYRIGHT * These drawings including design idea and construction techniques herin are the sole property of Aqua Logic Inc. They shal not be revised, copied, or reproduced in an AQUA LOGIC ULTRAVIOLET STERILIZERS manner without the written consent of Aqua Logic Inc..



9558 Camino Ruiz, San Diego, CA 92126

ALSH-2DX THRU 8 UV SPECIFICATIONS

SHEET # DRAWN BY DATE REVISION

DRAWING #