



### WATER-COOLED DELTA STAR HEAT PUMP SPECIFICATIONS

MODEL NO.	HP/TONS	NOMINAL BTUH	VOLTS / PHASE	AMPS.	WATTS	L	W	H	W2	WO	WI	R134A REFRIGERANT CHARGE (OZ.)	*CITY WATER USE (GPM)	WC WATER IN/OUT (FPT)	WATER FLOW RATE (GPM)	WEIGHT (LBS.)	SHIPPING WEIGHT (LBS.)	SHIPPING DIMENSIONS (INCHES)
DSHP-4WC	1/3	4,050	115	5.4	621	19"	20"	15"	1 1/2"	8"	4"	24	.5-1.5	3/4	8-15	70	85	23x24x19
DSHP-5WC	1/2	6,000	115	9.5	1092	24"	20"	17"	3"	10"	5"	30	.7-2	1 1/2	12-25	100	119	33x26x25
DSHP-6WC	1/2	6,000	230/1	4.8	1104	24"	20"	17"	3"	10"	5"	30	.7-2	1 1/2	12-25	100	119	33x26x25

\* CITY WATER USE BASED ON 55-60°F WATER TEMPERATURE ENTERING THE UNIT. WATER FLOWS THROUGH UNIT ONLY WHEN THE UNIT IS RUNNING. IN THE CHILLING MODE THE WATER GPM USE IS ON THE LOW END AND IN THE HEATING MODE THE GPM USE IS ON THE HIGH END. MAKE SURE THE WATER SUPPLY THE RECOMMENDED GPM ON HIGH END OR HIGHER.

ALL DIMENSIONS ARE APPROXIMATE AND COULD CHANGE WITHOUT NOTICE

 <small>Aquatic Design Manufacturing &amp; Integration</small>	Aqua Logic, Inc. 9558 Camino Ruiz San Diego, CA. 92019		
<b>TITLE: DSHP-4WC THRU DSHP-6WC          WATER-COOLED DELTA STAR HEAT          PUMP SPECIFICATIONS</b>			
LAST UPDATE: 4-29-14	DATE: 4-28-06	FILE: DSHP-4,5 & 6 WC SPEC	BY CE